



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical

**Catalog Number:** 15B159

**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
015W3000RG (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [015W3000RG](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Difference In "B" - External Buss May Need Adjustment

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B159	110kV	21 in.	21 in.	30.38 in.	13.88 in.	5.88 in.	9.25 in.	6	.875 slots in.	N/A
015W3000RG	110kV	21 in.	21 in.	30.375 in.	21.266 in.	5.062 in.	9.25 in.	6	0.875 in.	20.469 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B159	6.12 in.	N/A	NA in.	7.88 in.	3-12x3.25	4 hole spade 1.75x1.25
015W3000RG	10.641 in.	5.750 in.	N/A	13.641 in.	3.0-12x3.50, SP x 12un-2a	(4) .562 hole (1) blade 1 blade in.4 holes

**Cable Adapter:** NONE

**Flange Adanter:** NONE