



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 15B167
Voltage Class (kV): 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4000	
015W4000UW (Amps)		4000	

General Comments:

Replacement Information

ABB Style Number: [015W4000UW](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: (A) Adjust line bus. (See B dimension) (B) Confirm CT's if present will fit bushing. (See D dimension)

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B167	110kV	21 in.	21 in.	34.312 in.	16.125 in.	5.625 in.	10.875 in.	6	.875 in.	N/A
015W4000UW	110kV	21 in.	21 in.	34.312 in.	24.36 in.	6.116 in.	10.875 in.	6	0.625 in.	22.606 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B167	6.125 in.	6.25 in.	N/A	9.125 in.	4.0-10x4.188	(4) .688 hole blade
015W4000UW	12.047 in.	6.5 in.	N/A	15.235 in.	4.0-10x4.25 x	(4) .688 hole blade, 4.25 x 3.5 x .750 N/A

Cable Adapter: NONE

Flange Adapter: NONE