



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B168  
**Voltage Class (kV):** 23      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4000	
025W4000RH (Amps)		4000	

**General Comments:** GE Type LC Bushing

**Replacement Information**

**ABB Style Number:** [025W4000RH](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Difference In "B" - External Buss May Need Adjustment - due to site glass Note - Replacement for Vertical Mounting Only

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B168	150kV	21 in.	21 in.	34.312 in.	18.25 in.	6.125 in.	10.876 in.	6	.875 in.	N/A
025W4000RH	150kV	20.75 in.	20.75 in.	34.313 in.	24.312 in.	6.125 in.	10.875 in.	6	0.625 in.	22.594 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B168	9.125 in.	7.875 in.	in.	11.125 in.	4-10x4.25	(4) .688 hole blade, .750 thick
025W4000RH	12.031 in.	6.5 in.	N/A	15.219 in.	4.0-10 x 4.25, SP x	(4) .688 hole blade, .750 thick N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE