



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 15B17
Voltage Class (kV): 34 **BIL (kV):** 200

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 1200 | |
| 034W1200AT (Amps) | | 1200 | |

General Comments:

Replacement Information

ABB Style Number: [034W1200AT](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" Dimension and "D" Dimension, Confirm If Acceptable

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|--------|--------|------------|------------|-----------|-------------|--------------|--------------------|----------|
| 15B17 | 200kV | 21 in. | 21 in. | 32.5 in. | 19.75 in. | 3.5 in. | 7.25 in. | 4 | .875 in. | N/A |
| 034W1200AT | 200kV | 21 in. | 21 in. | 32.531 in. | 26.188 in. | 3.605 in. | 7.25 in. | 4 | 0.875 in. | 29.5 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|-----------|---|-----------|-------------------------------|--------------------------------------|
| 15B17 | 13.81 in. | 4 in. | N/A | 15.56 in. | 1.5 - 12 x 2.125 | 1.5-12 x 2.188 |
| 034W1200AT | 14.625 in. | 3.875 in. | N/A | 17 in. | 1.5-12x2.250, SP x | 1.5-12X3.25 N/A |

Cable Adapter: NONE

Flange Adapter: NONE