



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B173  
**Voltage Class (kV):** 34      **BIL (kV):** 200

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4000	
034W4000RV (Amps)		4000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [034W4000RV](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Difference In "B" Dimension, External Buss May Need Adjustment

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B173	200kV	21 in.	21 in.	34.31 in.	22.63 in.	6.63 in.	10.875 in.	6	0.88 in.	N/A
034W4000RV	200kV	21 in.	21 in.	34.312 in.	32.547 in.	6.695 in.	10.875 in.	6	0.875 in.	37.875 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B173	13.75 in.	7.75 in.	n/a in.	15.5 in.	4.0-10 4.0 in usable thread	(4) 0.688 holes in 0.75 thk spade
034W4000RV	18.047 in.	7.50 in.	N/A	21.047 in.	4.0-12x4.25 x	(4) .688 hole blade N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE