



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical

**Catalog Number:** 15B19

**Voltage Class (kV):** 46 **BIL (kV):** 250

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	1200
046W0412UL (Amps)	400	1200	1200

**General Comments:**

**Replacement Information**

**ABB Style Number:** [046W0412UL](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Note Difference in "B" - External Bus May Need Adjusted

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B19	250kV	16.5 in.	16.5 in.	33.5 in.	24.69 in.	5 in.	8.25 in.	4	.875 in.	N/A
046W0412UL	250kV	16.5 in.	16.5 in.	33.5 in.	28.765 in.	4.12 in.	8.25 in.	4	0.875 in.	39.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B19	18.69 in.	5 in.	N/A	20.44 in.	1.5-12 x 2.125	1.5-12 x 1.56
046W0412UL	18.443 in.	4.875 in.	24.453 in.	20.818 in.	1.5-12X2.25 x 12 UN-2A	1.5-12x2.25, .875 id tube .875 in.I.D. Tube

**Cable Adapter:** NONE

**Flange Adapter:** NONE