



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B3
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400		
025W0400AW (Amps)	400		

General Comments:

Replacement Information

ABB Style Number: [025W0400AW](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" - External Buss May Need Adjusted Note Cable Adapter is required. Note that the existing cable adapter must be cut and new one brazed

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B3	150kV	21 in.	21 in.	27.5 in.	16 in.	3.125 in.	7.25 in.	4	.875 in.	N/A
025W0400AW	150kV	21 in.	21 in.	27.531 in.	20.25 in.	3.219 in.	7.25 in.	4	0.875 in.	20.625 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B3	9.188 in.	4 in.	12.375 in.	10.938 in.	1.125-12x2.0	.875 id tube
025W0400AW	10.75 in.	3.875 in.	21.406 in.	13.125 in.	1.125-12x2.25 x 12 UN-2A	.875 id tube .875 dia in.I.D. Tube

Cable Adapter: 7647C57H05

Flange Adapter: NONE