



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B300BB  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		14000	
025T1400HB (Amps)		14000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T1400HB](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B300BB	150kV	0 in.	21 in.	33.25 in.	21.13 in.	13.56 in.	21 in.	12	.875 slots in.	30 in.
025T1400HB	150kV	N/A	21 in.	33.25 in.	21.125 in.	13.562 in.	21 in.	12	0.875 in.	30 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B300BB	11.13 in.	15.75 in.	N/A	15.38 in.	4- (10) hole spades, .688 holes	2- (6) hole spades, .688 holes
025T1400HB	11.125 in.	17.125 in.	N/A	15.38 in.	(10) .688h/b(4)b x	(6).688h/bld (2)bld N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE