



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B301  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4500	
025T0450JB (Amps)		4500	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T0450JB](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B301	150kV	21 in.	21 in.	32.5 in.	18 in.	8.25 in.	12.25 in.	6	.875 slots in.	28.5 in.
025T0450JB	150kV	21 in.	21 in.	32.531 in.	17.969 in.	8.24 in.	12.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B301	11.13 in.	8.75 in.	N/A	13.13 in.	2- (6) hole spades, .688 holes	1- (4) hole spade, .688 holes
025T0450JB	11.094 in.	8.75 in.	N/A	13.094 in.	(6).688 h/b (2)bld, SP x	(4) .688 hole (1) blade, TP N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE