



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 15B303

Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		7500	
025V0750VZ (Amps)		7500	

General Comments: Vertical mounting only. Type "T" BB = Gray

Replacement Information

ABB Style Number: [025V0750VZ](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Vertical mounting only.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B303	150kV	21 in.	21 in.	32.5 in.	18 in.	9.5 in.	13.25 in.	6	.875 slots in.	26 in.
025V0750VZ	150kV	21 in.	21 in.	32.531 in.	17.969 in.	9.528 in.	13.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B303	11.13 in.	9.875 in.	N/A in.	13.13 in.	(6) .688 holes per blade, (4) blades, SP	(6) .688 holes per blade, (1) blade (2) blades
025V0750VZ	11.094 in.	9.875 in.	N/A	13.094 in.	(6).688 holes per blade, (4) blades, SP x	(6) .688 hole per blade, (1) blade, 0.750 Thick N/A

Cable Adapter: NONE

Flange Adapter: NONE