



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical

**Catalog Number:** 15B304BB

**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		10000	
025T1000JK (Amps)		10000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T1000JK](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B304BB	150kV	21 in.	21 in.	32.5 in.	18 in.	11.5 in.	15.75 in.	8	.875 slots in.	28.5 in.
025T1000JK	150kV	21 in.	21 in.	32.656 in.	17.844 in.	11.588 in.	15.75 in.	8	0.875 in.	28.75 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B304BB	11.125 in.	12.375 in.	N/A	13.13 in.	4- (8) hole spades, .688 holes	2- (6) hole spades, .688 holes
025T1000JK	11.094 in.	12.375 in.	N/A	12.969 in.	(8).688h/b (4)bld, SP x	(6).688 holes per blade, (2) blades N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE