



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 15B308
 Voltage Class (kV): 25 BIL (kV): 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		18000	
025U1800VC (Amps)		18000	

General Comments:

Replacement Information

ABB Style Number: [025U1800VC](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B308	150kV	21 in.	21 in.	32.5 in.	18 in.	15.75 in.	21 in.	12	.875 slots in.	30 in.
025U1800VC	150kV	21 in.	21 in.	32.531 in.	17.969 in.	15.708 in.	21 in.	12	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B308	11.13 in.	N/A	N/A	13.13 in.	4- (12) hole spades, .688 holes	
025U1800VC	11.094 in.	15.5 in.	N/A	13.094 in.	(12) .688 holes/blade (4) blades x	(8).688 holes/blade (2) blades N/A

Cable Adapter:

NONE

Flange Adapter:

NONE