



**Original Bushing Information**

Original Bushing Manufacturer: G.E. Mounting Position:  
 Catalog Number: 15B311  
 Voltage Class (kV): 25 BIL (kV): 150

|                       |          |                  |                     |
|-----------------------|----------|------------------|---------------------|
| Application           | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) |          | 4500             |                     |
| 025U0450JL (Amps)     |          | 4500             |                     |

**General Comments:**

**Replacement Information**

ABB Style Number: [025U0450JL](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

**Notes/Comments:**

| Catalog Number | BIL   | EL    | CT    | L        | B      | D         | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep    |
|----------------|-------|-------|-------|----------|--------|-----------|-------------|--------------|--------------------|----------|
| 15B311         | 150kV | 0 in. | 3 in. | 15.5 in. | 19 in. | 7.19 in.  | 11.25 in.   | 6            | .875 slots in.     | 28.5 in. |
| 025U0450JL     | 150kV | 0 in. | 3 in. | 15.5 in. | 19 in. | 7.188 in. | 11.25 in.   | 6            | 0.875 in.          | 28.5 in. |

| Catalog Number | Strike     | P Dia.   | Cable Height/Pin Height for AB Bushing - CH | LHV        | Top Terminal Threads (inches)  | Bottom Terminal Thread/Configuration |
|----------------|------------|----------|---|------------|--------------------------------|--------------------------------------|
| 15B311         | 11.13 in.  | N/A      | N/A   | 14.13 in.  | 2- (6) hole spades, .688 holes |                                      |
| 025U0450JL     | 11.125 in. | 7.75 in. | N/A   | 14.125 in. | (6).688 h/b (2) bld x          | (4) .688 hole blade<br>N/A           |

Cable Adapter:

NONE

Flange Adapter:

NONE