



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B311BB
Voltage Class (kV): 25 **BIL (kV):** 150

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 4500 | |
| 025T0450JL (Amps) | | 4500 | |

General Comments:

Replacement Information

ABB Style Number: [025T0450JL](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|-------|-------|----------|--------|-----------|-------------|--------------|--------------------|----------|
| 15B311BB | 150kV | 0 in. | 3 in. | 15.5 in. | 19 in. | 7.19 in. | 11.25 in. | 6 | .875 slots in. | 28.5 in. |
| 025T0450JL | 150kV | 0 in. | 3 in. | 15.5 in. | 19 in. | 7.188 in. | 11.25 in. | 6 | 0.875 in. | 28.5 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|----------|---|------------|--------------------------------|--------------------------------------|
| 15B311BB | 11.13 in. | N/A | N/A | 14.13 in. | 2- (6) hole spades, .688 holes | 1- (4) hole spade, .688 holes |
| 025T0450JL | 11.125 in. | 7.75 in. | N/A | 14.125 in. | (6).688 h/b (2) bld x | (4) .688 hole blade N/A |

Cable Adapter:

NONE

Flange Adapter:

NONE