



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B312BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		6000	
025T0600JD (Amps)		6000	

General Comments:

Replacement Information

ABB Style Number: 025T0600JD **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B312BB	150kV	0 in.	3 in.	15.5 in.	19 in.	8.25 in.	12.25 in.	6	.875 slots in.	26 in.
025T0600JD	150kV	0 in.	3 in.	15.5 in.	18.969 in.	8.24 in.	12.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B312BB	11.25 in.	N/A	N/A	14.13 in.	4- (6) hole spades, .688 holes	1- (4) hole spade, .688 holes
025T0600JD	11.094 in.	8.75 in.	N/A	14.094 in.	(6).688 holes per blade, (4) blades, SP x	(4) .688 hole per blade, (1) 1.25 thk blade, TP N/A

Cable Adapter:

NONE

Flange Adapter:

NONE