



**Original Bushing Information**

Original Bushing Manufacturer: G.E. Mounting Position:  
 Catalog Number: 15B314BB  
 Voltage Class (kV): 25 BIL (kV): 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		12000	
025T1200HJ (Amps)		12000	

**General Comments:**

**Replacement Information**

ABB Style Number: [025T1200HJ](#) Alternate ABB Style Number:

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B314BB	150kV	0 in.	3 in.	15.53 in.	18.97 in.	11.25 in.	15.75 in.	8	.875 slots in.	28.94 in.
025T1200HJ	150kV	0 in.	3 in.	15.531 in.	18.969 in.	11.5875 in.	15.75 in.	8	0.875 in.	28.938 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B314BB	11.125 in.	12.375 in.	N/A	14.13 in.	4- (10) hole spades, .688 holes	2- (6) hole spades, .688 holes
025T1200HJ	11.094 in.	12.375 in.	N/A	14.094 in.	(10) .688 holes per blade, (4) blades, SP x 10 Holes/Pad	(6) .688 holes per blade, (2) blades .688 dia in.