



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 15B332BB
 Voltage Class (kV): 25 BIL (kV): 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		6000	
025T0600VG (Amps)		6000	

General Comments:

Replacement Information

ABB Style Number: [025T0600VG](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B332BB	150kV	21 in.	21 in.	32.5 in.	18 in.	9.5 in.	13.25 in.	6	.875 in.	28.5 in.
025T0600VG	150kV	21 in.	21 in.	32.5 in.	18 in.	9.528 in.	13.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B332BB	11.125 in.	9.875 in.	N/A	13.125 in.	(6) .688 holes/blade (4) blades	(4) .688 hole single copper blade
025T0600VG	11.125 in.	9.875 in.	N/A	13.125 in.	(6).688 h/b (4) bld x	(4) .688 hole blade N/A

Cable Adapter: NONE
 Flange Adapter: NONE