



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B411BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4500	
025T0450HW (Amps)		4500	

General Comments:

Replacement Information

ABB Style Number: 025T0450HW **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B411BB	150kV	0 in.	11 in.	23.5 in.	19 in.	7.188 in.	11.25 in.	6	.875 slots in.	28.5 in.
025T0450HW	150kV	0 in.	11 in.	23.5 in.	19 in.	7.188 in.	11.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B411BB	11.13 in.	N/A	N/A	14.13 in.	2- (6) hole spades, .688 holes	1- (4) hole spade, .688 holes
025T0450HW	11.125 in.	7.75 in.	N/A	14.125 in.	(6) .688 holes per blade, (2) blades x	(4) .688 hole blade N/A

Cable Adapter:

NONE

Flange Adapter:

NONE