



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B428BB  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	
025T0120HK (Amps)		1200	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T0120HK](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B428BB	150kV	10 in.	10 in.	18.81 in.	20.94 in.	4.69 in.	10.25 in.	6	0.875 slots in.	17.5 in.
025T0120HK	150kV	0 in.	10 in.	18.812 in.	20.969 in.	4.699 in.	10.25 in.	6	0.875 in.	17.969 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B428BB	8.06 in.	5.88 in.	N/A	13.06 in.	1.5-12 x 2.125	1.5-12 x 2.125
025T0120HK	8.094 in.	5.875 in.	N/A	13.094 in.	1.5-12X2.25 x 12 UN-2A	1.5012x2.125 1.500 in.12 UN-2A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE