



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B430BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
025T0300HS (Amps)		3000	

General Comments:

Replacement Information

ABB Style Number: [025T0300HS](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B430BB	150kV	10 in.	10 in.	20.94 in.	20.61 in.	4.69 in.	10.25 in.	6	0.875 slots in.	17.97 in.
025T0300HS	150kV	0 in.	10 in.	20.937 in.	20.593 in.	4.688 in.	10.25 in.	6	0.875 in.	17.969 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B430BB	8.09 in.	5.875 in.	N/A	13.09 in.	3.0-12x3.125	3.0-12x4.188
025T0300HS	8.093 in.	5.875 in.	N/A	13.093 in.	3.0-12x3.125 x 12 UN - 2A	3.0-12x4.188 3.000 in.12 UN - 2A

Cable Adapter:

NONE

Flange Adapter:

NONE