



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 15B431
 Voltage Class (kV): 34 BIL (kV): 200

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	
034U0120HA (Amps)		1200	

General Comments:

Replacement Information

ABB Style Number: [034U0120HA](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B431	200kV	10 in.	10 in.	20.812 in.	24.94 in.	4.625 in.	10.25 in.	6	.875 slots in.	27.5 in.
034U0120HA	200kV	N/A	10 in.	20.812 in.	24.969 in.	4.699 in.	10.25 in.	6	0.875 in.	27.25 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B431	12.06 in.	5.875 in.	N/A	17.06 in.	1.5-12 x 2.125	1.5-12 x 2.125
034U0120HA	12.094 in.	5.875 in.	N/A	17.094 in.	1.5-12X2.25 x 12 UN-2A	1.5-12x2.125 1.500 in.12 UN-2A

Cable Adapter:

NONE

Flange Adapter:

NONE