



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B432BB
Voltage Class (kV): 34 **BIL (kV):** 200

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 2000 | |
| 034T0200HB (Amps) | | 2000 | |

General Comments:

Replacement Information

ABB Style Number: [034T0200HB](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|--------|--------|------------|------------|-----------|-------------|--------------|--------------------|------------|
| 15B432BB | 200kV | 10 in. | 10 in. | 20.812 in. | 24.94 in. | 4.625 in. | 10.25 in. | 6 | .875 slots in. | 27.5 in. |
| 034T0200HB | 200kV | N/A | 10 in. | 20.821 in. | 23.672 in. | 4.699 in. | 10.25 in. | 6 | 0.875 in. | 27.277 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|-----------|---|------------|-------------------------------|--------------------------------------|
| 15B432BB | 12.06 in. | 5.875 in. | N/A | 17.06 in. | 1.5-12 x 2.125 | 1.5-12 x 2.125 |
| 034T0200HB | 12.094 in. | 5.875 in. | N/A | 17.094 in. | 2.0-12x2.5 x 12 UN-2A | 2.0-12x2.125 2.000 in.12 UN-2A |

Cable Adapter:

NONE

Flange Adapter:

NONE