



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Horizontal  
**Catalog Number:** 15B440BB  
**Voltage Class (kV):** 15      **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3100	
025T0320KC (Amps)		3200	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T0320KC](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B440BB	110kV	10 in.	10 in.	20.94 in.	20.56 in.	4.688 in.	10.25 in.	6	.88 slots in.	N/A
025T0320KC	150kV	10 in.	10 in.	20.937 in.	20.609 in.	4.7 in.	10.25 in.	6	0.875 in.	17.969 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B440BB	8.06 in.	5.875 in.	N/A	13.06 in.	3-12 x 3.0	3-12x4.25
025T0320KC	8.093 in.	5.875 in.	N/A	13.093 in.	3.0-12x3.125 SP x	3.000-12UN-2A, 4.188 USABLE THD N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE