



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B602BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		6000	
025T0600VE (Amps)		6000	

General Comments:

Replacement Information

ABB Style Number: [025T0600VE](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B602BB	150kV	21 in.	21 in.	32.5 in.	22.38 in.	9.5 in.	13.25 in.	6	.875 slots in.	N/A
025T0600VE	150kV	21 in.	21 in.	32.5 in.	22.375 in.	9.528 in.	13.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B602BB	11.25 in.	N/A	N/A	13.13 in.	4- (6) hole spades, .688 holes	1- (4) hole spade, .688 holes
025T0600VE	11.125 in.	9.875 in.	N/A	13.125 in.	(6).688 holes per blade, (4) blades, SP x	(4).688 hole blade N/A

Cable Adapter:

NONE

Flange Adapter:

NONE