



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.    **Mounting Position:**  
**Catalog Number:** 15B603  
**Voltage Class (kV):** 25    **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		7500	
025U0750VF (Amps)		7500	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025U0750VF](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B603	150kV	21 in.	21 in.	32.5 in.	22.38 in.	9.5 in.	13.25 in.	6	.875 slots in.	N/A
025U0750VF	150kV	21 in.	21 in.	32.5 in.	22.375 in.	9.528 in.	13.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B603	11.25 in.	N/A	N/A	13.13 in.	4- (6) hole spades, .688 holes	
025U0750VF	11.125 in.	9.875 in.	N/A	13.125 in.	(6).688 h/b (4)bld x	(6).688 hole blade, .750 thick N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE