



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 15B605BB  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		12000	
025T1200VH (Amps)		12000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T1200VH](#) **Alternate ABB Style Number:** [025U1200VH](#)

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B605BB	150kV	21 in.	21 in.	32.5 in.	22.38 in.	13.56 in.	18.5 in.	12	.875 slots in.	28.5 in.
025T1200VH	150kV	21 in.	21 in.	32.531 in.	22.344 in.	13.648 in.	18.5 in.	12	0.875 in.	30 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B605BB	11.13 in.	14.63 in.	N/A	13.13 in.	4- (10) hole spades, .688 holes	2- (6) hole spades, .688 holes
025T1200VH	11.094 in.	14.625 in.	N/A	13.094 in.	(10) .688 h/b (4) b SP x	(6) .688 h/b (2)b N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE