



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B606BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		14000	
025T1400WM (Amps)		14000	

General Comments:

Replacement Information

ABB Style Number: [025T1400WM](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B606BB	150kV	21 in.	21 in.	32.5 in.	22.38 in.	13.56 in.	18.5 in.	12	.875 slots in.	28.5 in.
025T1400WM	150kV	21 in.	21 in.	32.531 in.	22.344 in.	13.648 in.	18.5 in.	12	0.875 in.	30 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B606BB	11.13 in.	14.63 in.	N/A	13.13 in.	4- (10) hole spades, .688 holes	2- (6) hole spades, .688 holes
025T1400WM	11.094 in.	14.625 in.	N/A	13.094 in.	(10).688 h/b (4)b x	(6) .688 h/b (2)b 2 Pads, 6 Holes/Pad in.

Cable Adapter:

NONE

Flange Adapter:

NONE