



**Original Bushing Information**

**Original Bushing Manufacturer:** Locke **Mounting Position:** Vertical  
**Catalog Number:** 15B61  
**Voltage Class (kV):** 69 **BIL (kV):** 350

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400		
069Z0400UP (Amps)	400		

**General Comments:**

**Replacement Information**

**ABB Style Number:** 069Z0400UP **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Difference in "Tube ID" - Confirm fit of draw lead cable Note Differences in "B" - External Buss may need adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B61	350kV	21 in.	21 in.	35 in.	36.875 in.	5.25 in.	9.25 in.	6	.875 in.	N/A
069Z0400UP	350kV	21.656 in.	21.656 in.	34.75 in.	34.438 in.	4.893 in.	9.25 in.	6	0.875 in.	72.28 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B61	27.18 in.	6 in.	33.26 in.	30.19 in.	1.125-12 X 2.125	1.25 ID TUBE
069Z0400UP	24.906 in.	5.75 in.	31.094 in.	26.656 in.	1.125-12 x 2.25 x	.875 I/D tube N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE