



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 15B611BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4500	
025T0450HP (Amps)		4500	

General Comments:

Replacement Information

ABB Style Number: 025T0450HP **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B611BB	150kV	3 in.	3 in.	15.5 in.	23 in.	7.19 in.	11.25 in.	6	.875 slots in.	28.5 in.
025T0450HP	150kV	N/A	3 in.	15.531 in.	22.969 in.	7.21 in.	11.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B611BB	11.13 in.	N/A	N/A	13.13 in.	2- (6) hole spades, .688 holes	1- (4) hole spade, .688 holes
025T0450HP	11.094 in.	7.75 in.	N/A	13.094 in.	(6).688 holes per blade, (2) blades, SP x	(4) .688 hole per blade, (1) blade, TP N/A

Cable Adapter: NONE

Flange Adapter: NONE