



**Original Bushing Information**

Original Bushing Manufacturer: G.E.      Mounting Position: Vertical  
 Catalog Number: 15B615BB  
 Voltage Class (kV): 25      BIL (kV): 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		12000	
025T1200WS (Amps)		12000	

**General Comments:**

**Replacement Information**

ABB Style Number: [025T1200WS](#) Alternate ABB Style Number:

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Note Difference in Top Terminal Hole Spacing

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B615BB	150kV	3 in.	3 in.	15.5 in.	23 in.	11.5 in.	15.75 in.	8	.875 in.	N/A
025T1200WS	150kV	3 in.	3 in.	15.531 in.	22.969 in.	11.58 in.	15.75 in.	8	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B615BB	11.125 in.	12.375 in.	N/A	13.125 in.	(12).688 holes per blade, (4) blades, SP	(2) .688 holes per blade, (2) blades
025T1200WS	11.094 in.	12.375 in.	N/A	13.094 in.	(10).688 holes per blade, (4) blades, SP x	(2) .688 holes per blade, (2) blades N/A

Cable Adapter: NONE

Flange Adapter: NONE