



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 15B619BB  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		21500	
025T2150HM (Amps)		21500	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025T2150HM](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B619BB	150kV	0 in.	10 in.	22.5 in.	28.688 in.	15.75 in.	21 in.	12	.875 slots in.	28.5 in.
025T2150HM	150kV	10 in.	10 in.	22.531 in.	28.657 in.	15.708 in.	21 in.	12	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B619BB	11.13 in.	17.125 in.	N/A	15.38 in.	14 hole spades (4)	10 hole spades (2) .688 holes 1.75 c-c
025T2150HM	11.094 in.	15.500 in.	N/A	15.344 in.	(14) .688 h/b (4) blades, SP x 14 Holes/Pad	(10) .688 h/b (2)b 2 Pads in.10 Holes/Pad

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE