



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 17B252BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
025W3000BF (Amps)		3000	

General Comments:

Replacement Information

ABB Style Number: [025W3000BF](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B252BB	150kV	21 in.	21 in.	34.3 in.	22.4 in.	4.75 in.	9.25 in.	6	.88 slots in.	21.4 in.
025W3000BF	150kV	21 in.	21 in.	34.312 in.	22.422 in.	4.699 in.	9.25 in.	6	0.875 in.	21.875 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B252BB	12 in.	6 in.	NA in.	15 in.	3.0-12x3	spade 0.688 holes(2) 1.75 on
025W3000BF	12.297 in.	5.75 in.	N/A	15.297 in.	3.0-12x3.125, SP x 12 UN-2A	(2) .688 hole blade .688 dia in.

Cable Adapter:

NONE

Flange Adapter:

NONE