



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 17B352BB  
**Voltage Class (kV):** 34      **BIL (kV):** 200

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
034W3000BC (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [034W3000BC](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B352BB	200kV	21 in.	21 in.	34.31 in.	26.25 in.	4.63 in.	9.25 in.	6	0.875 in.	N/A
034W3000BC	200kV	21 in.	21 in.	34.312 in.	26.297 in.	4.7 in.	9.25 in.	6	0.875 in.	31.188 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B352BB	18.875 in.	5.875 in.	N/A	18.875 in.	3-12 x 3.75	(2) .688 hole blade
034W3000BC	16.297 in.	5.875 in.	N/A	19.172 in.	3.0-12x3.125 x 12 UN-2A	(2) .688 hole blade 0.688 dia in.

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE