



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 17B402BB

Voltage Class (kV): 46 **BIL (kV):** 250

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400	1200	1200
046W0412AU (Amps)	400	1200	1200

General Comments:

Replacement Information

ABB Style Number: [046W0412AU](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B402BB	250kV	16.5 in.	16.5 in.	33.5 in.	35.188 in.	4 in.	8.25 in.	4	.875 in.	N/A
046W0412AU	250kV	16.5 in.	16.5 in.	33.5 in.	31.188 in.	4.12 in.	8.25 in.	4	0.875 in.	39.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B402BB	N/A	4.875 in.	30.750 in.	22.125 in.	1.5-12x2.25 SP	1.5-12x2.25/.875 id tube
046W0412AU	18.443 in.	4.875 in.	26.812 in.	20.818 in.	1.5-12X2.25, SP x 12 UN-2A	.875 id tube/1.5-12x 2.25 .875 in.I.D. Tube

Cable Adapter:

NONE

Flange Adapter:

NONE