



**Original Bushing Information**

Original Bushing Manufacturer: G.E. Mounting Position:  
 Catalog Number: 17B450BB  
 Voltage Class (kV): 46 BIL (kV): 250

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
046W2000UD (Amps)		2000	

**General Comments:**

**Replacement Information**

ABB Style Number: [046W2000UD](#) Alternate ABB Style Number:

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B450BB	250kV	21 in.	21 in.	34.75 in.	36.94 in.	5.25 in.	9.25 in.	6	.88 slots in.	56.9 in.
046W2000UD	250kV	21 in.	21 in.	34.703 in.	37 in.	5.15 in.	9.25 in.	6	0.875 in.	59.906 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B450BB	24.5 in.	N/A	NA in.	27.5 in.	2-12x2.88	2 hole spade 1.75x3.25 dia=0.69x1.75 on
046W2000UD	24.548 in.	5.75 in.	N/A	27.548 in.	2.000-12UN-2A, 2.625 USABLE THD, SP x 12 UN-2A	(2) .688 HOLES, (1) Bld ROTATED 30 DEG FROM TAP CL 1 Pad in.2 Holes/Pad