



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 17B501BB  
**Voltage Class (kV):** 25      **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400		
025W0412AT (Amps)	400	1200	1200

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025W0412AT](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B501BB	150kV	16.5 in.	16.5 in.	29.5 in.	21.44 in.	3.12 in.	7.25 in.	4	.88 slots in.	N/A
025W0412AT	150kV	21 in.	21 in.	29.531 in.	20.781 in.	3.219 in.	7.25 in.	4	0.875 in.	21 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B501BB	10.75 in.	N/A	16.88 in.	13.12 in.	1.5-12x2.12	1.5-12x2.25 0.88 tube ID
025W0412AT	10.687 in.	3.5 in.	16.282 in.	12.437 in.	1.5-12X2.25 usable, SP x 12 UN - 2A	1.5-12x2.25 usable , .875 id tube .875 in.

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE