



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 17B651BB
 Voltage Class (kV): 69 BIL (kV): 350

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 2000 | |
| 069W2000UZ (Amps) | | 2000 | |

General Comments:

Replacement Information

ABB Style Number: [069W2000UZ](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|----------|----------|----------|------------|---------|-------------|--------------|--------------------|------------|
| 17B651BB | 350kV | 16.5 in. | 16.5 in. | 34.5 in. | 41.19 in. | 6.5 in. | 10 in. | 6 | 0.875 in. | 72.46 in. |
| 069W2000UZ | 350kV | 16.5 in. | 16.5 in. | 34.5 in. | 41.233 in. | 6.5 in. | 10 in. | 6 | 1 in. | 73.406 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|-----------|---|------------|-------------------------------|---|
| 17B651BB | 27.38 in. | 6.75 in. | N/A | 30.75 in. | 2.0-12x2.5 | spade .688 holes 1.75 cntr-cntr |
| 069W2000UZ | 27.406 in. | 6.500 in. | N/A | 30.781 in. | 2.0-12 x 2.5 x 12 UN-2A | (2) .688 hole blade 1 Pad in.2 Holes/Pad |

Cable Adapter:

NONE

Flange Adapter:

NONE