



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**

**Catalog Number:** 17B668BB

**Voltage Class (kV):** 69      **BIL (kV):** 350

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
069W3000UL (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [069W3000UL](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
17B668BB	350kV	19 in.	19 in.	36.75 in.	42.75 in.	7.5 in.	10.88 in.	6	0.750 in.	73.8 in.
069W3000UL	350kV	19.5 in.	19.5 in.	36.781 in.	42.719 in.	7.5 in.	10.875 in.	6	0.75 in.	73.8 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
17B668BB	27.375 in.	7.5 in.	N/A	30.375 in.	3.0-12x3.0	(2) .688 holes 1.75 apart c/c
069W3000UL	27.406 in.	7.5 in.	N/A	30.406 in.	3.000-12UN-2A, 3.000 USABLE THD x 12 UN-2A	(2) .688 hole blade, .750 thick blade 1 Pad in. 2 Holes/Pad

**Cable Adapter:** NONE

**Flange Adapter:** NONE