



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 17B819
 Voltage Class (kV): 15 BIL (kV): 110

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 1200 | |
| 015W1200RQ (Amps) | | 1200 | |

General Comments:

Replacement Information

ABB Style Number: [015W1200RQ](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|-----------|-----------|------------|------------|-----------|-------------|--------------|--------------------|------------|
| 17B819 | 110kV | 26.75 in. | 26.75 in. | 34.375 in. | 17.75 in. | 3.13 in. | 7.25 in. | 3 | .625 holes in. | 14.07 in. |
| 015W1200RQ | 110kV | 26.75 in. | 26.75 in. | 34.428 in. | 17.719 in. | 3.125 in. | 7.25 in. | 3 | 0.625 in. | 14.375 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|-----------|-----------|---|------------|---------------------------------------|--------------------------------------|
| 17B819 | 7.94 in. | 4.25 in. | N/A | 11.82 in. | 1.5-12 x 2.125 | 1.125-12 x 2.75 |
| 015W1200RQ | 7.938 in. | 4.250 in. | N/A | 11.813 in. | 1.50-12UN-2A x 2.125 USABLE x 12un-2a | 1.125-12UN-2A 1.125 in.12un-2a |

Cable Adapter:

NONE

Flange Adapter:

NONE