



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:**  
**Catalog Number:** 1B560  
**Voltage Class (kV):** 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4500	
025J0450AM (Amps)		4500	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025J0450AM](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B560	150kV	N/A	N/A	16.75 in.	18.75 in.	6 in.	10.875 in.	6	.875 in.	22 in.
025J0450AM	150kV	N/A	N/A	16.875 in.	18.687 in.	6 in.	10.875 in.	6	0.875 in.	22 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B560	10.312 in.	N/A	N/A	14 in.	2- (6) hole spades, .688 holes	1- (3) hole spade, .688 holes
025J0450AM	10.312 in.	N/A	N/A	14 in.	2 Pads x 6 Holes/Pad	1 Pad .688 dia in.3 holes

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE