



**Original Bushing Information**

**Original Bushing Manufacturer:**                    **Mounting Position:** Horizontal

**Catalog Number:**                                    1B596

**Voltage Class (kV):**                                25        **BIL (kV):**                                150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		9500	
025V0900WR (Amps)		9000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [025V0900WR](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note differences in "L" "B" and "D" - Confirm fit, Buss May Need Adjusted Note difference in "P" - check gasket sealing surface Note flange adapter will be required.  
Note Difference in Current Rating

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B596	150kV	N/A	N/A	15.938 in.	17.875 in.	9.156 in.	14.25 in.	6	0.875 in.	N/A
025V0900WR	150kV	3 in.	3 in.	15.531 in.	22.969 in.	9.528 in.	13.25 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B596	10.25 in.	9.312 in.	N/A	13.187 in.	(8) .688 holes per blade, (4) blades, SP	(4).688 hole (2) blade
025V0900WR	11.094 in.	9.875 in.	N/A	13.094 in.	(8) .688 h/b (4)b x 8 Holes/Pad	(4) .688h/b (2) b .688 in.4/PAD

**Cable Adapter:** NONE