



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:**  
**Catalog Number:** 1B752  
**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400		
015K0060AT (Amps)	600		

**General Comments:**

**Replacement Information**

**ABB Style Number:** [015K0060AT](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B752	110kV	N/A	N/A	8.375 in.	13.19 in.	3.625 in.	7.25 in.	3	in.	N/A
015K0060AT	110kV	N/A	N/A	8.375 in.	11.688 in.	3.625 in.	7.25 in.	3	0.562 in.	13.875 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B752	N/A	N/A	N/A	N/A	1.125-12x2.25	none
015K0060AT	7 in.	3.875 in.	7.063 in.	8.438 in.	1.125-12x2.0 x 12un-2a	1.562 i.d. porcelain 1.562 in.I.D. Tube

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE