



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Horizontal  
**Catalog Number:** 1B827  
**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
015K0300AM (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [015K0300AM](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B827	110kV	N/A	N/A	9.19 in.	13.125 in.	3.625 in.	7.25 in.	3	.562 holes in.	14.1 in.
015K0300AM	110kV	N/A	N/A	9.219 in.	13.094 in.	3.734 in.	7.25 in.	3	0.562 in.	14.1 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B827	6.812 in.	3.88 in.	N/A	8.25 in.	1- (4) hole spade, .562 holes	2.0-12 x 3.688
015K0300AM	6.781 in.	3.875 in.	N/A	8.219 in.	(4).562 hole blade, SP x 4 holes	2.0-12x3.438, TP 2.000 in.12un-2a

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE