



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical  
**Catalog Number:** 1B879  
**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
015J0300AQ (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 015J0300AQ **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Adjust line bus. See B dimension. Confirm bushing will fit tank opening. See P dimension.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B879	110kV	17.75 in.	N/A	25.25 in.	13.062 in.	5 in.	8.5 in.	6	.625 in.	13.8 in.
015J0300AQ	110kV	17.75 in.	N/A	24.953 in.	12.234 in.	5.021 in.	8.5 in.	6	0.688 in.	13.812 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B879	6.188 in.	5.375 in.	N/A	8.188 in.	3.0-12x2.875	(4) .562 hole blade
015J0300AQ	6.359 in.	5.625 in.	N/A	8.234 in.	3.000-12UN-2A, 3.000 USABLE THD, SP x 12 UN-2A	(4) .562 hole blade, 1.000 thick, TP 1 Pad in.4 Holes/Pad

**Cable Adapter:** NONE

**Flange Adapter:** NONE