



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical  
**Catalog Number:** 1B969  
**Voltage Class (kV):** 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		6000	
025T0600VM (Amps)		6000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 025T0600VM **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Check "D" Dimension For Fit Through Apparatus and CT's Note Difference in "B" - External Buss May Need Adjusted Note Differences In "P" dimension, confirm if gasket space is acceptable.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
1B969	150kV	17 in.	17 in.	31.188 in.	18.375 in.	9.188 in.	13.75 in.	6	0.812 in.	N/A
025T0600VM	150kV	17 in.	17 in.	31.188 in.	19.937 in.	9.528 in.	13.75 in.	6	0.875 in.	28.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
1B969	8.938 in.	9.312 in.	N/A	11.563 in.	6.314"-6.318" SMOOTH W/2 GRVS	(6) .688 hole blade
025T0600VM	11.125 in.	9.875 in.	N/A	13.125 in.	6.314 - 6.318 dia. Smooth x	(6) .688 hole blade N/A

**Cable Adapter:** NONE