



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical

**Catalog Number:** 3B5

**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	400		
015W0400UE (Amps)	400		

**General Comments:**

**Replacement Information**

**ABB Style Number:** 015W0400UE **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Differences In "D" and "B" Dimensions, Confirm If Acceptable Note that original cable adapter needs cut and new one brazed Note cable adapter is required

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
3B5	110kV	20.75 in.	20.75 in.	25.25 in.	12.625 in.	2.38 in.	7.25 in.	3	.562 in.	N/A
015W0400UE	110kV	20.75 in.	20.75 in.	25.656 in.	18.938 in.	3.219 in.	7.25 in.	3	0.625 in.	14.375 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
3B5	6.13 in.	4.375 in.	9 in.	6.685 in.	1.125 - 12 x 2.125	875 id tube
015W0400UE	7.938 in.	4.375 in.	21 in.	11.813 in.	1.125-12x2.25 x 12un-2a	875 dia I.D. 875 in.I.D. Tube

**Cable Adapter:** 7647C57H06

**Flange Adapter:** NONE