



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical  
**Catalog Number:** 3B50  
**Voltage Class (kV):** 15 **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	
015W1200UZ (Amps)		1200	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [015W1200UZ](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Adjust line bus. See B dimension. Note difference in "D" - Confirm fit through CTs and Mounting Hole

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
3B50	110kV	20.75 in.	20.75 in.	28.38 in.	10.875 in.	2.38 in.	7.25 in.	3	.562 in.	N/A
015W1200UZ	110kV	20.75 in.	20.75 in.	28.375 in.	17.718 in.	2.75 in.	7.25 in.	3	0.625 in.	14.312 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
3B50	6.25 in.	4.375 in.	N/A	6.75 in.	1.5-12x2.12	1.125-12x3.12
015W1200UZ	7.937 in.	4.250 in.	N/A	11.812 in.	1.5-12x 2.250 USABLE THREAD x	1.125-12x1.375 USABLE THREAD N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE